

**SYSTEM AND METHOD FOR MULTI-CAMERA
LINKING AND ANALYSIS**

5 This patent application claims the benefit of U.S. Provisional Patent Application
No. 60/234,581, filed September 22, 2000, entitled "System and Method for Multi-
Camera Linking and Analysis", which is incorporated herein in its entirety, by
reference thereto.

10

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates generally to a system and method for tracking
objects, such as people, using one or more video cameras. In one embodiment, the
15 present invention may be used to track people through a retail environment.

2. Description of the Prior Art

Basic video tracking systems are well known in the art. The video tracking
20 systems previously known lack certain functional capabilities required for generating
accurate and comprehensive tracking information, especially while using multiple
video cameras.

Primarily to date, research and development has been focused on single camera
25 tracking solutions. For example, see Celenk et al. in a 1988 IEEE article entitled
"Moving Object Tracking Using Local Windows"; Tsai et al. in IEEE articles,
published in 1981, entitled "Estimating Three-Dimensional Motion Parameters Of A
Rigid Planar Patch, and Uniqueness" and "Estimation Of Three-Dimensional Motion
Parameters Of Rigid Objects With Curved Surfaces"; Liao in a 1994 article entitled
30 "Tracking Human Movements Using Finite Element Methods"; Montera et al. in a

1993 SPIE article entitled "Object Tracking Through Adaptive Correlation"; Burt et. al. in a 1989 article entitled "Object Tracking With A Moving Camera"; Sethi et al. in a 1987 article entitled "Finding Trajectories Of Feature Points In A Monocular Image Sequence"; and Salari et al. in a 1990 article entitled "Feature Point Correspondence In
5 The Presence Of Occlusion."

Q. Cai et al. in an article entitled "Automatic Tracking of Human Motion in Indoor Scenes Across Multiple Synchronized Video Streams" describes a method for object tracking through multiple cameras. This solution is limited by the fact that all
10 Single View Tracking systems must be accurately time synchronized in order to support accurate camera hand-off. Also, intensity features are used for camera-to-camera hand-off, even though in most applications intensity features will vary from camera to camera based on camera viewing perspective - one camera views the front of the object being tracked while the other views the back of the object being tracked.
15 This methodology may work well in simple environments with a limited number of cameras, but will likely not work well in complex environments and/or environments with a large number of cameras.

Robert B. Boyette, in United States patent 5,097,328, describes a system that
20 collects and reports information on the number of people in a queue, service time, and anticipated wait time in a queue for a bank branch. This system is limited by the fact that the average time in a queue is computed based on arrival rates and service times, not actual queue wait times, and as such is inaccurate. Also, since there is no record of individual customer activities, it is not possible generate reports with respect to a
25 person's sequence of activities, which can be used in identifying customer behavior.

There is a therefore need for a sophisticated, yet cost effective, tracking system that can be used in many applications. For example, it has become desirable to acquire information concerning the activity of people, for example, within a scene of a retail

establishment, a bank, automatic teller machines, bank teller windows, to name a few, using data gathered from analysis of video information acquired from the scene.

It is also desirable to monitor the behavior of consumers in various locations of a retail establishment in order to provide information concerning the sequence of events and decisions that a consumer makes. This information is useful in many situations, such as, to adjust the location and features of services provided in a bank, to change merchandising strategies and display arrangements; etc. Consequently, it is necessary for the system to differentiate between people in the scene and between people and other stationary and moving objects in the scene.

Given the size of these environments, a video tracking system is needed which can track the movement of objects, such as people, through multiple cameras. Moreover, this tracking system must support the capability to query track information in order to generate information that describes how people and the environment interact with one another.

SUMMARY OF THE INVENTION

The present invention is directed to a system and method for tracking objects, such as customers in a retail environment. The invention is divided into two distinct software subsystems, the Customer Tracking system and the Track Analysis system. The Customer Tracking system tracks individuals through multiple cameras and reports various types of information regarding the tracking function, such as location by time and real world coordinates. The Track Analysis system queries individual track data and generates reports about customer activity and behavior. Inputs to the Customer Tracking system are a set of analog or digital cameras that are positioned to view some physical environment. The output of the Customer Tracking system is a set of customer tracks that contain time and position information that describe the path that an individual took through the environment being monitored. The Track Analysis system

reads the set of customer tracks produced by the tracking system and interprets the activities of individuals based on user defined regions of interest (ROI). Examples of a region of interest are: (1) a teller station in a bank branch, (2) a check-out lane in a retail store, (3) an aisle in a retail store, and the like.

5

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram showing the overall architecture of the present invention, in one embodiment.

10 FIG. 2 is a flow diagram showing the overall flow of the present invention.

FIG. 3 depicts a region of interest (ROI) filter used in the present invention.

15 FIGS. 4-5 are flow diagrams depicting processes used for path linking in the present invention.

FIGS. 6-8 are diagrams depicting how the linking process may be performed in one embodiment.

20 FIGS. 9A, 9B and 10 are flow diagrams depicting processes used for path linking in the present invention.

FIGS. 11A, 11B and 11C depict example physical floor plans that may be used with the present invention.

25

FIGS. 12A and 12B are diagrams depicting certain calibration techniques that may be used with the present invention.

DETAILED DESCRIPTION OF THE INVENTION**1. Overall Architecture**

FIG. 1 illustrates the hardware components of the present invention, in one embodiment. The hardware components may be standard off-the-shelf components, and include one or more video cameras 110, one or more frame grabbers 120, and a processor 130, such as a personal computer (PC) or equivalent, having a memory 135 which stores software programs for controlling the processor 130. The combination of the video camera 110 and frame grabber 120 may collectively be referred to as an "image acquisition module" 145. The frame grabber 120 may receive a standard video signal output by the video camera 110, such as a RS-170, NTSC, CCIR, or PAL video signal, which can be monochrome or color. In a preferred embodiment, the video cameras 110 are mounted or positioned to view a selected viewing area or scene 150 of interest (region of interest – ROI), such as a checkout lane in a retail establishment, an automated teller machine (ATM), an entrance, an exit, or any other localized area where people or objects may move and/or interact with devices or other people or objects.

The frame grabber 120 is embodied, for example, by a Meteor™ Color Frame Grabber, available from Matrox. The frame grabber 120 operates to convert the analog video signal into a sequence or stream of digital video frame images that are stored within the memory 135, and processed by the processor 130. For example, in one implementation, the frame grabber 120 converts the video signal into a 2 x 2 sub-sampled NTSC image which is 320 x 240 pixels or a 2 x 2 sub-sampled PAL color image which is 384 x 288 pixels, or in general a W x L image defining a single video frame of video information. A variety of other digital image formats and resolutions are also suitable, as will be recognized by one of ordinary skill in the art. Each pixel of a video frame has a predetermined bit resolution, such as 8 bits, and color data may be

used to increase system performance. The digital information representing each video frame is stored in the memory 135 asynchronously and in parallel with the various processing functions described below.

5 **2. Customer Tracking**

 The entire video camera and processing system of FIG. 1 may be referred to herein as a Single Camera Tracking system 210. As shown in FIG. 2, a Customer Tracking system may be divided into two distinct subsystems: Single Camera Tracking
10 systems 210 and Path Linking system 220. The Single Camera Tracking system 210 generates path information for individuals as they move through a single camera 110 view in real-time.

 The path information for a single path may consist of an ordered set of data
15 elements. Each data element is composed of an x,y coordinate in image space, a camera 110 identifier, and a timestamp. The individual path is written to a consolidated path file 230 when the individual exits the camera 110 view or the path is broken.

 The Path Linking System 220 reads paths from the consolidated path file 230
20 generated by all Single Camera Tracking systems 210 over some period of time. The Path Linking system 220 may perform the following operations.

- Repairs broken tracks for an individual in a single camera 110 view.
- Links individual customer tracks across multiple cameras 110.
- 25 • Converts paths from an individual camera 110 coordinate system to a global real world coordinate system.

The output of the Path Linking System 220 is a real-world path file 240 containing path information describing an individual's path through a real world environment. The path information for a single path may consist of an ordered set of data elements, each of which is composed of an x,y coordinate in real world space and a timestamp.

In order to perform path linking 220, the following elements, explained in further detail below, are required as input:

- 10 • A database containing the following data (all explained in further detail later):
 - Camera calibration information, defined later in Multi-Camera Calibration and Transformation to Real World Coordinates.
 - 15 ○ Multi-camera calibration information, including the set of corresponding points across multiple camera views, defined later in Multi-Camera Calibration and Transformation to Real World Coordinates.
 - A set of Region of Interest (ROI) filters for each camera 110.
- 20 • A consolidated event/path file 230 containing the tracks (i.e. paths) generated from one or more Single Camera Tracking systems.

As output, the Path Linking System 220 provides a file 240 containing the set of linked paths translated into real world coordinates.

Region of interest (ROI) filters are required to address certain situations that create erroneous paths during the path linking process. Three types of ROI filters may be used:

- Exclusion Regions. Exclusion regions are rectangular areas where path linking is not allowed to occur. An example of an exclusion region is a camera boundary where there is no other overlapping camera. If a path of an individual exiting the camera 110 view coincides with the creation of a path of an individual entering a camera 110 view, the path linking system may attempt to link the two paths. This results in an erroneous link. By defining an exclusion region on the edge of a camera 110, path linking will not be allowed to occur in this area.
- Break Regions. Break regions are similar to exclusion regions in that they address locations in the camera view 110 where erroneous linking may occur. Break regions identify areas where it may be possible that a Single Camera Tracking system 210 may have created an erroneous link. Like exclusion regions, break regions are placed on camera 110 boundaries.
- Warping Region. A warping region defines an effective tracking area for a camera 110 view. This is defined in further detail below.

To allow a camera 110 to obtain as large a field of view as possible, wide-angle lenses are often used. Unfortunately, wide-angle lenses create significant warping near the corners of images. Paths that occur in these parts of an image are often noisy and inconsistent. A method has been developed, called the Warping Region of Interest (ROI) filter, which removes path segments that occur in these warped regions.

The Warping ROI filter is an elliptical mask that removes all parts of paths that lie outside the elliptical boundary. For each camera 110 view, a Warping ROI filter can be defined by specifying the center point, major axis size, and minor axis size for the

filter. In some instances, a filter may not be specified. The values for center, major, and minor axis are given in pixels.

A diagram illustrating an ROI filter 300 is provided in FIG. 3. The shaded area
5 301 indicates the region in which path information is retained. All paths or segments of paths that lie outside the shaded area 301 are removed when the paths are first read from the consolidated event file 230.

If the end of a path is very close to the edge of the ROI filter 300, it may not be
10 advisable to link the end of this path to a path beginning close to that same location in the same scene. For example, confusion may occur between one person exiting the camera 110 view and another person entering the same camera 110 view nearby. To avoid this confusion, the ROI filter 300 contains one additional parameter, called “fringe percentage”, which ranges from 0 to 1.0. This value makes it possible to tailor
15 the range of distances from the center of the ellipse within which the system will allow same scene linking to occur. A value of 1.0 means that same scene linking can occur anywhere in the ROI. A value of 0.75 indicates that same scene linking can only occur within 75% of the distance of the ROI center 302 to the edge. The boundary 303 represents a value of 1.0, which allows same scene linking anywhere in the ellipse. The
20 boundary 304 represents a value of 0.75, which allows same scene linking only within this area 304 of the ellipse.

The output file produced by the system is the linked path output file 240. This file contains no header information. Each path in the file may be stored in the
25 following format (as defined in PathLink.h).

- The Path ID (int)
- The number of points on the path (int)

- A character buffer of path points, where each path point is of type PL_InstanStruct, defined by:

```

struct PL_InstanStruct{
5         PL_IntPoint m_position;    // the real world position
        CTime m_time;               // the time instant of the point
        int m_pathID;               // a reference to the path ID
        };

```

where PL_IntPoint is defined by:

```

struct PL_IntPoint{
        int x;
        int y;
        };

```

Referring to FIG. 4, the Path Linking System 220 executes the following steps to perform path linking. Each step is explained in further detail later:

- [401] The parameter database is read.
- [402] The consolidated event file is read.
- [403] ROI filters, Warping, Exclusion, and Break filters, are applied.
- [404] Path linking mechanisms are selected.
- [405] Path linking and path breaking are performed for a predefined set of iterations.
- [406] Paths are converted to real world coordinates.
- [407] Real world path information is written to the output file.

In step 401, the parameter database is read to obtain the following information required by path linking and analysis:

- The number of camera 110 views.
- The camera 110 views.
- The calibration parameters for each camera 110 views.
- 5 • The multi-camera calibration information, including cross-camera calibration points for the set of camera 110 views.
- The ROI filters 300 parameters for each camera 110 views (if they exist).

10 In step 402, the consolidated event file 230 is read to obtain the track information generated by some number of Single Camera Tracking systems 210. Each track is read and stored as a *PL_Path* object. Each *PL_Path* object maintains the following information:

- 15 • The Path ID (int).
- A set of path elements, where each element is a *PL_Instnt*, described below.
- The Scene ID, or the single camera 110 view identifier, for the first point on the path (int).
- 20 • A flag indicating if the end of this path can be linked to a path in the same scene, called the *CanLinkToSameScene* (bool) flag. This is determined by the ROI Fringe Percentage parameter or the Exclusion ROI filter.
- A *PL_Path* pointer to a next path. This is the path to which the end of
- 25 the current path is linked. This pointer is assigned during the path linking process 220.

- A PL_Path pointer to a previous path. This is the path to which the beginning of the current path is linked. This pointer is assigned during the path linking process 220.
- The linking technique used to link to the next path (int). This value is assigned during the path linking process 220.
- The linking confidence for the link to the next path (double). This value is assigned during the path linking process 220.
- An indicator if this path is a duplicate path (bool). This value is assigned after path linking 220 using a separate routine that checks for duplicate paths.

A PL_Instant represents a particular point on the path. Each PL_Instant object contains the following information:

- The Scene ID (int).
- The feet position in image coordinates (PL_IntPoint, described previously).
- The centroid position in image coordinates (PL_IntPoint).
- The time at which the point occurs (CTime).

In step 403, as each path is read from the consolidated event file 230, filtering is applied. Paths are filtered using the ROI elliptical filter and/or by applying Break filters. With reference to FIG. 5, the process works as follows.

- [501] A single event file path is read in to temporary storage (such as memory 135).
- [502] A new PL_Path object is created.

[503] The event file track is traversed point by point. All points at the beginning of the event file track that are outside the elliptical region 300 or are within a break filter are discarded.

[504] The remaining points are traversed one by one. As long as a point is inside the elliptical region 300 and not within a break filter, it is added to the PL_Path object.

[505] If a point is found that is outside the elliptical region 300 or within a break filter, the current PL_Path object is completed and stored. A new PL_Path object is then created.

[506] The process loops to step 503, with the remaining event file path and the new PL_Path object.

By using the above process, a path that moves outside the elliptical region 300 and then moves back within the region will be split into two PL_Path objects.

Similarly, as a path moves into a Break Filter region and out of a break filter region, two PL_Path objects are created. All paths that lie entirely outside the elliptical region or completely within one or more Break Regions are removed.

After each of the PL_Path objects (or *paths*) are created, the last point of each path is tested against the Fringe Percentage (fp) value using the following formula:

$$\frac{(x - cx)^2}{a^2} + \frac{(y - cy)^2}{b^2} \leq fp$$

If this expression evaluates to TRUE, same scene linking is allowed for this path, and the CanLinkToSameScene flag is asserted in the PL_Path object. Otherwise, this flag is set false. Note that *a* is the major axis of the ellipse, and *b* is the minor axis value (in pixels).

A similar test is performed for exclusion regions. If the last point of the path lies within an exclusion region, scene linking is allowed for this path, and the CanLinkToSameScene flag is asserted in the PL_Path object.

5 In step 404, several mechanisms are present in the present invention. Each mechanism provides a unique methodology for determining whether two paths can be linked together. Some of the mechanisms work only on paths within a single scene, while other path linking mechanisms are used for paths that cross between multiple scenes. All of the mechanisms are parameterized to allow a configuration to determine
10 the range of conditions under which they are applicable.

Each path linking returns the following structure:

```
15 struct PL_LinkResult
{
    unsigned int m_resultFlags;
    double m_value;
    double m_confidence;
};
```

20 The *m_resultFlags* variable contains information about whether the paths could be successfully linked, or if not, the reason for failure. The *m_value* variable contains additional information about the failure mode, such as the actual real-world distance or time distance recorded between the two paths being tested for linking. If linking is
25 possible for the two paths, the variable *m_confidence* contains a value between 0.0 and 1.0 that indicates the confidence that these two paths can be linked together given this path linking method and its associated parameters. Descriptions of the available path linking mechanisms are presented below.

Scene path linking mechanisms are employed only when two paths both occur in the same scene, or camera 110 view. Two such mechanisms are available:

- IterTimeDistance_Scene
- IterOverlap_Scene

The *Iter* prefix indicates that each of these methods can be repetitively applied to already linked paths to build longer linked paths. The *_Scene* suffix indicates that these methods apply only to paths in the same Scene.

This first Scene linking mechanism is IterTimeDistance_Scene. This method fixes simple path breaks in which a person is being tracked, the track disappears for a few seconds, and then the path reappears.

Provided with two paths, this method determines if the endpoint of the first path is sufficiently close in time and distance (hereby called the *time-space bubble*) to the start point of the second path. Time is measured in seconds and distance is measured in inches. The conversion from an image coordinate space to a real world coordinate space is described in Multi-Camera Calibration and Transformation to Real World Coordinates. If it is sufficiently close, the paths can be linked.

The following parameters are provided to this mechanism:

- The maximum time difference in seconds.
- The maximum spatial distance in inches
- A boolean flag indicating whether distance should be measured using the foot position of the two points, or the centroid position (TRUE = centroid, FALSE = foot).

- The maximum confidence value that can be returned by this method for the smallest possible time-distance difference.
- The minimum confidence value that can be returned by this method for the largest possible time-distance difference (within the maximum time-space bubble).

Referring to FIG. 6, the end point 601 of Path 1 (602) and the start point 603 of Path 2 (604) fall within the an acceptable distance, as denoted by the time-space bubble 605 in this figure. If $(T2 - T1) < \text{Max Time}$, then the two paths can be linked.

The returned confidence value is generated using the following formula:

$$RC = \text{Min Conf} + ((\text{Max SD} - \text{Actual SD}) / \text{Max SD}) * (\text{Max Conf} - \text{Min Conf})$$

Where:

- RC is the returned confidence value.
- Min Conf is the minimum confidence parameter provided to the function as input.
- Max SD is the maximum spatial distance parameter provided to the function as input.
- Actual SD is the actual computed spatial distance (in inches) between the end point of the first path, and the start point of the second path.
- Max Conf is the maximum confidence parameter provided to the function as input.

The second scene linking mechanism is IterOverlap_Scene. This method fixes more complex path breaks that occur when an individual being tracked separates into two coexisting tracks. It is desirable for the two tracks to be merged into a single track, since there is really only one person. A diagram showing each of two possible cases that can occur is shown in FIG. 7:

In FIG. 7, Path 1 (701) and Path 2 (702) demonstrate one possible case. An individual being tracked from point a to point b breaks up into two paths at point c, generating Path 1 (701) and Path 2 (702). Path 1 (702) and Path 2 (702) overlap in time, so IterTimeDistance_Scene cannot link the paths, yet somehow these two paths must be linked together to get the full path for the individual. IterOverlap_Scene provides this linking capability.

Paths 3 (703) and 4 (704) represent another case. An individual being tracked from point d to point e breaks up into two paths at point f, generating Paths 3 (703) and 4 (704). However in this case, Path 3 (703) disappears after a short time, and Path 4 (704) remains. We do not need to link these two paths together, but would prefer to label Path 3 (703) as a duplicate path, and only retain Path 4 (704). IterOverlap_Scene will not link these paths, allowing another mechanism (described later) to label Path 3 (703) as a duplicate, and remove it from consideration.

For two paths that overlap in time, IterOverlap_Scene compares the real-world distance in inches between the two paths for each shared time instant. If at any point during the shared time of existence the distance between the paths is greater than a maximum value, the paths cannot be linked.

The following parameters are provided to this mechanism:

- The maximum spatial distance in inches.

- A boolean flag indicating whether distance should be measured using the foot position of the two points, or the centroid position (TRUE = centroid, FALSE = foot).
- The maximum confidence value that can be returned by this method for the smallest possible distance difference.
- The minimum confidence value that can be returned by this method for the largest possible distance difference.

If the two paths can be linked, the returned confidence value is generated using the following formula:

$$RC = \text{Min Conf} + ((\text{Max SD} - \text{Worst SD}) / \text{Max SD}) * (\text{Max Conf} - \text{Min Conf})$$

Where:

- RC is the returned confidence value.
- Min Conf is the minimum confidence parameter provided to the function as input.
- Max SD is the maximum spatial distance parameter provided to the function as input.
- Worst SD is the worst actual computed spatial distance (in inches) between any pair of points (one from each path) that share the same time instant.
- Max Conf is the maximum confidence parameter provided to the function as input.

Site path linking mechanisms are employed only when two paths both occur in the different scenes. Three such mechanisms are available:

- IterTimeDistance_Site
- IterOverlap_Site
- IterOverTimeShift_Site

5

The *Iter* prefix indicates that each of these methods can be repetitively applied to already linked paths to build longer linked paths. The *_Site* suffix indicates that these methods apply to paths that cross multiple Scenes.

10

The first site linking mechanism is TimeDistance_Site. This method fixes simple path breaks in which a person is being tracked, the track disappears for a few seconds, and then the path reappears across scene boundaries. It is analogous (input, output, and methodology) to IterTimeDistance_Scene, except that it works for paths that cross between multiple Scenes.

15

The second site linking mechanism is IterOverlap_Site. This method fixes more complex path breaks that occur when an individual being tracked separates into two coexisting paths and these paths cross scene boundaries. It is desirable for the two paths to be merged into a single path, since there is really only one person. It is analogous (input, output, and methodology) to IterOverlap_Scene, except that it works for paths that cross between multiple Scenes.

20

The third site linking mechanism is IterOverTimeShift_Site. This method fixes more complex path breaks that occur when an individual being tracked separates into two coexisting paths and these paths cross scene boundaries. It is desirable for the two paths to be merged into a single path, since there is really only one person.

25

IterOverTimeShift_Site also handles slight timing variations that may occur between scenes residing on two different PCs 130. Since each PC 130 has its own clock, it is necessary to synchronize the clocks across the site so that paths in the consolidated event file have consistent time stamps. Since it still may be possible for different PCs 130 to have a slight clock skew (2 secs or less), this is included to correct this problem.

The methodology used for IterOverTimeShift_Site is very similar to IterOverlap_Site with one exception. The user provides a time shift value to the function. The function then (in essence) shifts all the points on one of the paths in time by the time shift value before performing the IterOverlap_Site.

If at any point during the shifted-shared time of existence the distance between the paths is greater than a maximum distance value, the paths cannot be linked. However, another condition is also placed on the paths before success is determined. The average distance between the two paths during the shifted-shared time of existence is also determined. If this value is greater than half of the maximum distance value, the paths cannot be linked. The combination of these two conditions allows the user to specify a looser maximum distance (because the difference between PC times is not precise, and therefore the distance may be way off for one or two points), since the average distance test will help insure that the paths are close together overall.

The following parameters are provided to this mechanism:

- The time shift value in seconds (usually 1 or -1).
- The maximum spatial distance in inches.

- A boolean flag indicating whether distance should be measured using the foot position of the two points, or the centroid position (TRUE = centroid, FALSE = foot).
- The maximum confidence value that can be returned by this method for the smallest possible distance difference.
- The minimum confidence value that can be returned by this method for the largest possible distance difference.

If the two paths can be linked, the returned confidence value is generated using the following formula:

$$RC = \text{Min Conf} + ((\text{Max SD} - \text{Worst SD}) / \text{Max SD}) * (\text{Max Conf} - \text{Min Conf})$$

Where:

- RC is the returned confidence value.
- Min Conf is the minimum confidence parameter provided to the function as input.
- Max SD is the maximum spatial distance parameter provided to the function as input.
- Worst SD is the worst actual computed spatial distance (in inches) between any pair of points (one from each path) that share the same time instant.
- Max Conf is the maximum confidence parameter provided to the function as input.

After the path linking methods have been selected, the system of the present invention iteratively performs path linking and path breaking. This process is

performed repeatedly so that the system has the opportunity to build up larger paths than could not possibly be generated in a single pass.

Consider the single scene example of FIG. 8. Paths 1 (801), 2 (802) and 3 (803)
5 all represent the same individual who has broken up into three distinct tracks. Path 2 (802) is a subset of Path 1 (802), so IterOverlap_Scene will think it is a duplicate path and not link them together. However, Path 3 (803) and Path 2 (802) will be linked by IterOverlap_Scene because they are sufficiently close and overlap in time. Therefore, after the first iteration of path linking, there are two paths (Path 1, and Path 2+3) that
10 represent a single person. If path linking is performed one more time, IterOverlap_Scene will be able to link Path 1 with Path 2+3, to yield a single path for the individual.

The path linking algorithm is an optimization technique that employs the
15 confidence values generated by the path linking mechanisms to find the best set of linked paths across the entire set of scenes, or camera 110 views. The following describes the path linking algorithm.

With references to FIGS. 9A and 9B, the path linking algorithm is separated
20 into two main sections. In the first section, paths are tested to determine if they can be linked. In some cases, multiple paths may be able to link to the same path, causing a conflict. In the second section of this algorithm, the conflicts are resolved and the final path linking assignments are determined.

25 First Section: Path Testing

[901] The list of all paths is filtered in the following manner. Paths that are in the middle of larger linked paths are filtered out, because they have been linked in a previous pass of the algorithm.

[902] Data elements from each path in the filtered path list are extracted and cached for rapid access during the optimization process. The elements include: the last point on each path, and the total path length of each cache.

[903] The filtered path list is sorted twice. The first sorted list, called
5 *endTimeSortedPaths* is the filtered path list sorted by the time of the last point of each path. The second sorted list, called *startTimeSortedPaths* is the filtered path list sorted by the time of the first point of each path. Sorting the filtered path list allows for more rapid comparisons during optimization.

[904] A data structure, *resultSet*, is initialized. For each filtered path, *resultSet*
10 contains the list of all possible paths that this path can link to (called *currentInfoArray*), as determined by testing all path pairs in the loop below.

[905] The paths on the *endTimeSortedPaths* list are iteratively compared to the paths on the *startTimeSortedPaths* list. This is accomplished by two loops, with
15 *endTimeSortedPaths* list in the outside loop and *startTimeSortedPaths* list in the inside loop. Each comparison executes the following steps on a pair of paths, one selected from *endTimeSortedPaths*, called *endpath*, and the other selected from *startTimeSortedPaths*, called *startpath*.

[905A] The first point on *startpath* is compared to the last point on *endpath*. If
20 the time between the two points is positive and too large, the inner loop is broken. This indicates that *endpath* ends well before *startpath* starts, so no further paths on *startTimeSortedPaths* list should be considered link candidates for *endpath*.

[905B] Conversely, if the time between the two points is negative, and the
25 magnitude is sufficiently large, *startpath* is skipped. This indicates that *startpath* starts well before *endpath* ends, so it is unreasonable to believe that these two paths could be linked together.

[905C] If *endpath* and *startpath* are not in the same Scene and are not in Scenes that border each other, then *startpath* is skipped because no linking is possible.

[905D] The first point on *endpath* is compared to the the last point on *startpath*.
5 If the time between the two points is positive and too large, then *startpath* is skipped. This indicates that *endpath* starts after *startpath* ends, so no linking is possible.

[905E] Finally, the same Scene linking test is executed. If *endpath* ends in the same Scene that *startpath* starts, and same Scene linking is not allowed for *endpath* (as determined by the Fringe Percentage), then *startpath* is skipped.
10

[905F] If all the tests above are passed successfully, then the two paths are subjected to the path linking mechanisms to see if the paths can actually be linked together. Based on the whether or not the paths are within a single Scene or cross multiple Scenes, the algorithm automatically selects which set of available path linking mechanisms to apply. The mechanisms are then applied individually. The result from the mechanism that returns the highest confidence is retained.
15

[905G] If the paths can be linked together then *startpath* is added to the list of paths to which *endpath* can link. This information is added to *currentInfoArray*, which is an element of *resultSet*.
20

[906] For each path, *currentInfoArray* now contains the list of paths to which it can link. *currentInfoArray* is sorted, with the best possible link placed on the top of the list.
25

Second Section: Conflict Resolution

- [911] The information in *currentInfoArray* is converted into a new structure called *conflictSet*. This structure contains a set of *conflictLists*, one for each filtered path. For a given path, *conflictList* represents all the paths that have selected that path as the most likely next path for linking. In other words, each path on a *conflictList* would like to assign its next *PL_Path* pointer to the given path. For a given path, if *conflictList* contains only one path, then there is no conflict for that path and the link is assigned.. If there are multiple paths on the list, the optimization algorithm must determine which path to select as the final link assignment.
- [912] The following iteration occurs to make final path assignments for those *conflictLists* that contain multiple paths. The iteration continues until all assignments are made.
- [912A] All of the *conflictLists* with multiple paths in *conflictSet* are searched to find the path that has the highest link confidence. There may be multiple paths that have the same link confidence. Each of these paths are added to a cleaned list called *resultList*.
- [912B] Each path on *resultList* is iteratively examined.
- [912B-1] If a path on the list has no alternative paths to link to (determined by examining *currentInfoArray* for that path), it is automatically selected as the best path for linking and the iteration stops.
- [912B-2] If all paths have second choices, the path with the largest confidence difference between the current choice and its second choice is selected as the best path for linking.
- [912C] Once a path is selected, all other candidates on the current *resultList* are not allowed to link to this path, so the next best paths are determined for

each of these paths by examining their *currentInfoArrays*. The corresponding resultLists are updated to include these paths.

[913] Once the final path assignments have been made, each *PL_Path* object that has a new next path is updated to reflect:

- 5 • The next *PL_Path* pointer (and that paths previous *PL_Path* pointer).
- The link confidence.
- The link method used.

[914] All newly linked paths are examined for loops (A->B->C->A). If these occur, they are broken (A->B->C).

10

Path linking is not perfect. It may link together paths that represent two people, creating an error condition. To compensate for this potential problem, a path breaking algorithm is executed after each path linking iteration to remove links that have a sufficient likelihood of being in error. Path breaking compares two paths at a time, looking closely at the areas in which linking has occurred on the two paths. It there may be confusion due to close proximity (within a time-space bubble) between links on both paths, the algorithm breaks each paths' links at the point of possible confusion.

15

Path breaking requires the following parameters:

20

- A time maximum in seconds (int).
- A distance maximum in inches (int).
- A (bool) flag to indicate whether the centroid (TRUE) or the foot position (FALSE) is used.

25

With respect to FIG. 10, the algorithm performs the following steps.

[1001] The list of links for each pair of paths is determined.

[1002] Each point before and after a link for one path is compared to each point before and after a link for the second path. If the points are sufficiently close, within the time-space bubble as determined by the parameters, then both paths are broken at that link.

5 [1003] If the paths are broken, new paths are formed at the break point.

Multi-Camera Calibration and Transformation to Real World Coordinates

In order to determine the real world distance in inches of a location in one camera to the same camera or a second camera, a mechanism to convert from an image space coordinate system to a real world coordinate space is required. The following procedure defines how to create this transformation. The following procedure takes into account that in a multi-camera system 210, the relation between cameras 110 is most important on overlapping cameras. If different cameras 110 do not overlap, it doesn't make sense to try to precisely relate the tracks' relative positions and directions.

1. The number of cameras to use is selected, and each is installed according to plans, taking care to leave a significant view overlap (i.e. 15%) whenever tracking has to be continued from one camera scene to another. The cameras should be in their final position.
2. Calibrate each camera individually, with the well known procedure defined in United States Patent 6,185,314, System and Method for Matching Image Information to Object Model Information.). Once this procedure is performed, each camera will have an associated set of measures:

- Camera Declination Angle, in radians: θ
- Camera Height, in inches: h
- Image Width semi-Angle, in radians: Δ

- Image Height semi- Angle, in radians: α
- Camera Focal Length, in inches: d

Using these parameters, for any camera, any point's Image Coordinates
 5 can be transformed into (camera's local) Real World Coordinates, with:

$$y_{rw} = h / [\tan(\theta - \beta)] ; \quad \text{where } \beta = \arctan([(y_{center} - y) \tan(\alpha)] / y_{center})$$

$$x_{rw} = D_h * (x - x_{center}) * \tan(\Delta) / x_{center} ; \quad \text{where } D_h = \sqrt{y_{rw}^2 + h^2}$$

10 And Real World Coordinates can be transformed into Image Coordinates, with:

$$y = y_{center} - [y_{center} / \tan(\alpha)] * \tan[\theta - \arctan(h / y_{rw} y)]$$

$$15 \quad x = [x_{rw} / D_h] * [x_{center} / \tan(\Delta)] + x_{center}$$

For each pixel to be transformed from image to real-world coordinates
 there is a resolution error associated with it. This error, given in inches, is
 calculated as follows: Transform all 4-connected pixels around the pixel under
 20 study, to obtain their real-world coordinates. Then compute the distance from
 each of the resultant 4 points to the point of interest, and choose the maximum
 as the error. This error accounts for both errors in mouse clicking and errors in
 location given by not enough resolution of the images. The more distant is a
 given point from the camera, the largest will be its associated error.

- 25
3. Select one camera as the "main" camera. All other cameras' coordinates and
 orientation will be relative to this camera. Enumerate all cameras. The main
 camera should be #1.

4. Steps 4 and 5 first described using 2 points in the overlap areas, then extended to N points. Mark 2 points at the main camera scene. One displays an image, and with the mouse, the user should click first on the first point and then on the corresponding second point. The program then calculates the (local) real world coordinates for these points, (x_1, y_1) and (x_2, y_2) , by the transformation given in step (2.) [Note, from this point forward, the sub-indexes to indicate “real-world” have been removed, since all of the coordinates refer to real-world coordinates.] The program then requests the global (that is, not relative to the local camera scene, but to the actual floor) real world coordinates of these points, which should be assigned or measured by hand: (X_1, Y_1) , (X_2, Y_2) . The camera orientation ω of this camera with respect to the global real world coordinate system is then calculated as:

$$\omega = \text{atan2}\{ (Y_2 - Y_1) / (X_2 - X_1) \} - \text{atan2}\{ (y_2 - y_1) / (x_2 - x_1) \}$$

And the origin (X_{gc}, Y_{gc}) of this camera’s real-world coordinate system in terms of the global system is calculated by:

$$X_{gc} = X_1 - x_1 \cos(\omega) + y_1 \sin(\omega)$$

$$Y_{gc} = Y_1 - y_1 \cos(\omega) - x_1 \sin(\omega)$$

5. For all the other camera scenes, the orientation and position of the camera will be obtained relative to another camera’s coordinate system, already known, presenting some overlap with this camera view.

The procedure is as follows: One possible implementation displays 2 images on the screen. The program asks the user to mark, in both images, point 1, and then, point 2. The coordinates are then transformed into (local) real-world

coordinates. Thus, we have: For the camera under calibration, (x_1, y_1) and (x_2, y_2) , and for the camera already calibrated, (X_1, Y_1) , (X_2, Y_2) . From here, ω , the angle of the new camera in terms of the other one, is calculated as:

$$\omega = \text{atan2}\{ (Y_2 - Y_1)/(X_2 - X_1) \} - \text{atan2}\{ (y_2 - y_1)/(x_2 - x_1) \}$$

And the origin of the local coordinate system (X_c, Y_c) of the new camera relative to the local coordinate system of the other one is given by:

$$X_c = X_1 - x_1 \cos(\omega) + y_1 \sin(\omega)$$

$$Y_c = Y_1 - y_1 \cos(\omega) - x_1 \sin(\omega)$$

6. The position and orientation of all cameras with respect to the global coordinate system can be obtained by summing the angles and local origin coordinates of all cameras used to calibrate the specified camera. Recursively:

$$\omega_N = \omega_{N-1} + \omega_N$$

$$\mathbf{X}_{Nc} = \mathbf{X}_{(N-1)c} + X_{Nc} * \cos(\omega_{N-1}) - Y_{Nc} * \sin(\omega_{N-1})$$

$$\mathbf{Y}_{Nc} = \mathbf{Y}_{(N-1)c} + Y_{Nc} * \cos(\omega_{N-1}) + X_{Nc} * \sin(\omega_{N-1})$$

Where boldface refers to absolute coordinates, and N is the number of camera scenes used to calibrate the current (thus N^{th}) camera. For example, if a camera is the 3rd in the path from the main camera, its absolute parameters will be calculated as follows:

$$\omega_3 = \omega_1 + \omega_2 + \omega_3$$

$$\mathbf{X}_{3c} = \mathbf{X}_{1c} + X_2 * \cos(\omega_1) - Y_2 * \sin(\omega_1) + X_3 * \cos(\omega_1 + \omega_2) -$$

$$Y_3 * \sin(\omega_1 + \omega_2)$$

$$Y_{3c} = Y_{1c} + Y_2 * \cos(\omega_1) - X_2 * \sin(\omega_1) + Y_3 * \cos(\omega_1 + \omega_2) - \\ X_3 * \sin(\omega_1 + \omega_2)$$

7. The results of this multi-camera calibration procedure are incorporated into the
 5 actual Path Linking system. Each single camera descriptor could have a list of
 the other systems that overlap with its view, and a simple transformation to go
 back and forth between both local real-world coordinate systems, given by a
 rotation and a translation.

10 As mentioned previously, each point in real-world coordinates has an associated
 resolution error, which can contribute to errors in the calculation of relative angles and
 relative coordinate origins on multi-camera calibration.

15 In order to estimate errors, the two main equations for calculating the origin
 location and orientation of a camera in terms of its "parent" camera are restated, with a
 more suitable notation:

$$\omega = \text{atan2} \{ (Q.y - P.y) / (Q.x - P.x) \} - \text{atan2} \{ (q.y - p.y) / (q.x - p.x) \}$$

$$20 \quad X_c = P.x - p.x * \cos(\omega) + p.y * \sin(\omega) \\ Y_c = P.y - p.y * \cos(\omega) - p.x * \sin(\omega)$$

Where points "p" and "q" are the two points for the camera under calibration and "P"
 and "Q" are the 2 points for the camera already calibrated. [Coordinates for any point
 25 "p" are indicated as (p.x, p.y)].

Consider one of the terms for ω :

$$\text{atan2} \{ (Q.y-P.y)/(Q.x-P.x) \}$$

Each point has an associated error in inches. With respect to FIG. 12A, these errors can be represented by circles 1201 of given radius around the points. The maximum error in angle is represented. As shown in FIG. 12B, by redrawing it, we can calculate its value.

The angular error will be given by

$$\sin[\varepsilon(P) + \varepsilon(Q)]$$

And the max. error in ω :

$$\varepsilon\{\omega\} = \sin[\varepsilon(P) + \varepsilon(Q)] + \sin[\varepsilon(p) + \varepsilon(q)]$$

The error on X_c will be given by:

$$\varepsilon\{X_c\} = \varepsilon\{P\} + \varepsilon\{p\} * \text{MAX}\{|A-A_p|, |A-A_m|\},$$

where:

$$A = \cos(\omega) - \sin(\omega)$$

$$A_p = \cos(\omega + \varepsilon\{\omega\}) - \sin(\omega + \varepsilon\{\omega\})$$

$$A_m = \cos(\omega - \varepsilon\{\omega\}) - \sin(\omega - \varepsilon\{\omega\})$$

And a similar error is defined for Y_c .

It is expected that by using more points in the overlapping areas to perform multi-camera calibration, the results will be more accurate. One approach for using more than two points is to make use of the formulations for 2 points, selecting pairs of points at a time, and averaging the results to obtain the more accurate calibration parameters.

If N points are selected in the overlap area between two camera 110 scenes, the procedure for obtaining the average orientation angle ω of the camera 110 under calibration with respect to the camera 110 already calibrated will be to first obtain ω using points 1 and 2, then using points 1 and 3, ... then using points 1 and N, then
 5 points 2 and 3, ... and then points N-1 and N, and to average the results to obtain the estimated orientation angle ω . However, averaging angles directly turns out to be a difficult task giving rise to several kinds of problems. One possible problem, for instance, is the following: Assume we are trying to average two angles that differ by 2
 10 degrees: $\omega=179$ and $\omega=-179$. The arithmetic average turns out to be zero, while our desired result is clearly 180 degrees. Our approach instead adds the angles vectorially, and then takes the resultant angle as the average.

The procedure in pseudocode is:

15 For i = 1 to N-1,
 For j = i to N,
 $\omega = \text{getOmega}(p[i], p[j], P[i], P[j])$; (PROCEDURE
 DESCRIBED BEFORE.)
 $x = x + \cos(\omega)$
 $y = y + \sin(\omega)$
 20 end
 end
 $\omega = \text{atan2}(y/x)$

The calculation of the average relative X_c and Y_c coordinates of the origin of the camera scene under calibration relative to the camera scene already calibrated does not present any problem when using N points in the overlapping areas, so a regular averaging can be performed:

5

For $i = 1$ to N ,

$X_c = X_c + \text{getXc}(p[i], P[i], \text{omega})$ (ALREADY

DESCRIBED)

$Y_c = Y_c + \text{getYc}(p[i], P[i], \text{omega})$ ‘ ‘

10

End

$X_c = X_c / N$

$Y_c = Y_c / N$

15

From probability theory, it is known that if we have N independent and identically distributed random variables with mean μ and standard deviation σ , its average will have a mean μ as well, but its standard deviation will be reduced to σ/\sqrt{N} . Although this concept cannot be applied directly to our calculations since the system is dealing with maximum errors instead of standard deviations and we do not have iid variables, intuition tells us that the errors will be reduced in a similar form in which the standard deviation is reduced, in general, unless the maximum possible error happen to occur in each of our terms, something very unlikely.

20

T estimated maximum error for an average is defined as the maximum error for any individual term divided by the square root of the number of terms in our calculation. The choice of the maximum of the individual error is made to be safe (the errors for each of the terms is different). This is the way in which errors due to resolution are estimated in our calibration procedure.

25

It is possible that other kinds of errors are present in our calculations, giving rise to errors larger than the estimated maximum errors described above. These errors might have several causes, among those, there are: errors produced in calibration of individual camera system, producing erroneous values for the θ , α , Δ , and h parameters
 5 for the camera, non-accounted image warping, etc.

During multicamera calibration, when calculating angles or offset origins using points or pairs of points, if differences larger than the maximum estimated errors are observed (between calculations with different points or pairs of points), it is assumed
 10 that other kind of error has occurred, and the maximum estimated error itself is set to this observed value.

3. Track Analysis

15 The path input file 240 is the output of the path linking step 220. Each path in the file is stored in the following format.

- The Path ID (int)
- The number of points on the path (int)
- 20 • A character buffer of path points, where each path point is of type PL_InstantStruct, defined by:

```

    struct PL_InstantStruct{
        PL_IntPoint m_position;    // the real world position
        CTime m_time;             // the time instant of the
    point
    int m_pathID;                 // a reference to the path
    ID
    };
  
```

25

where PL_IntPoint is defined by:

```
struct PL_IntPoint{
    int x;
    int y;
};
```

5

The Track Analysis subsystem provides the following capabilities:

10

- Interprets a single path in terms of what areas in the scene the person visited and how long they remained in that area. For example, when a person entered or exited a queue. The output is a simple report of areas visited and length of time an area was visited.
- Grouping of tracks based on common behaviors or activities. For example, identify all tracks of people that visited a product display.
- Filtering of spurious tracks based on various constraints, i.e. discarding tracks of people that did not originate or terminate from a point of ingress or egress.

15

In order to perform Path/Track Analysis, the following elements, explained in detail below, are required as input:

20

- A floorplan that consists of a jpeg or bitmap file rendering of the physical environment being monitored with the video cameras, with each pixel representing some number of inches in the floorplan, i.e. a scale specifier.
- An Analysis Region database that defines the type and location of regions, areas of interest, on the floorplan.
- A real world path file 240.

25

On output, the Track Analysis system may provide.

- A report of where individuals went and spent time in the physical environment.
- A report of the number of individuals to visit an area, as well as various statistics with regards to amount of time spent in the area.
- A file that consists of paths sharing a common behavior.
- Other relevant analytical information.

The path input file is the output of the path linking step (240). Each path in the file may be stored in the following format.

- The Path ID (int)
- The number of points on the path (int)
- A character buffer of path points, where each path point is of type PL_InstantStruct, defined by:

```

struct PL_InstantStruct{
    PL_IntPoint m_position;    // the real world position
    CTime m_time;             // the time instant of the
    point
    int m_pathID;              // a reference to the path
    ID
};

```

where PL_IntPoint is defined by:

```

struct PL_IntPoint{
    int x;
    int y;
};

```

};

The floorplan for the physical environment can be created with any tool that allows an end user to create a floorplan which is drawn to a real world scale. An example tool is Microsoft Visio 2000. The purpose of the floorplan is so that analysis regions of interest can be created and referenced in the context of the real world environment being monitored. FIG. 11A depicts a sample floorplan diagram 1100 for a bank branch.

Referring to FIG. 11B, an individual path 1101 can be overlayed in the context of the floorplan. 1102 represents the start of the path and 1103 represents the end of the path.

Analysis regions are areas in the floorplan where specific types of customer activities may occur. For example, the area around a teller window where people are served may be an analysis region. A queue area is a second example of an analysis region. Any number of arbitrary regions can be defined with respect to the floorplan. For example, in a retail store, a region may represent a complete department, a category of products, such as softdrinks, or a specific set of products, such as Coke.

Regions can be depicted in the shape of a rectangle or an ellipse, denoting an area of interest on the floorplan. A graphical example of several analysis regions is shown in FIG. 11C. In this figure, the ellipses 1105 represent teller locations and the rectangle 1106 represents a queue. It is now possible to analyze the individual paths within the context of the analysis regions. This process is described in further detail later.

An analysis region can be represented by the following data structure.

```

int      nID;           // region identifier
Rect     rect;          // rectangle descriptor
Ellipse  ellipse;       // ellipse descriptor
CString  sDescription;  // region descriptor
5  Int    nType;         // Rectangle/Ellipse

```

An individual path is an ordered list of tuples containing the following information.

10 <timestamp, x-coordinate, y-coordinate>

The first tuple is referred to as the point or origin for the path. The last tuple is referred to as the termination point for the path. By simple analysis of the point of origin, termination point, and consecutive tuples in the list, it is possible to make the

15 following observations.

- If a path at some time T1 is outside of an Analysis Region and at T1 + 1 is inside of the Analysis Region, then the path is said to have ***Entered*** the Analysis Region at time T1+1.
- 20 • If a path is inside an Analysis Region at time T1 and is outside of the Analysis Region at time T1+1, then the path is said to have ***Exited*** the Analysis Region at time T1+1.
- If a path originated at time T1 and is inside of the Analysis Region, then the path is said to have ***Started*** in the Analysis Region at time T1.
- 25 • If a path terminated at time T1 and is inside of the Analysis Region, then the path is said to have ***Ended*** in the Analysis Region at time T1.

The following algorithm is used to generate a track report.

```

N = number of samples
for ( i = 0; i < n; i++ )
{
    5      time = timestamp for point I
           x = current x-coordinate
           y = current y-coordinate

           // determine location
           thisRegion = -1;
           for ( j = 0; j < m; j++ )
           {
               10      if ( point(x,y) is inside Region[j] )
                           {
                               15      thisRegion = j;
                                   }
                           }
           // Determine if an event should be output
           if ( lastRegion != thisRegion )
           {
               20      if ( lastRegion != -1 )
                           output: Exited Region lastRegion at time
                           if ( thisRegion != -1 )
                               {
                                   25      if ( i = 0 )
                                               output: Started Region thisRegion at time
                                               else
                                               output: Entered Region thisRegion at time
                               }
                                   }
           }
           30      }
lastRegion = thisRegion;
}
if (lastRegion != -1 )
    output: Ended Region thisRegion at time

```


For the previous example floorplan and path, the output record set would contain the following.

Entered Queue 1106 at T1
 Exited Queue 1106 at T2
 Entered Teller 1105 at T3
 Exited Teller 1105 at T4

One obvious limitation of the algorithm above is that if an individual passes through a region for only a short period of time, the event is reported. For example, an individual may pass through multiple teller regions when walking to the teller that will ultimately provide the service. In general, a mechanism is required to filter false events that may be caused by individuals passing through a zone for a short period of time. Two methods may be used: applying a time threshold and/or detecting a *Stop* state.

A time threshold can be associated with each region such that an event is reported only if the path remains in the region for some time greater than N seconds. This time is computed by subtracting the time of the *Entered* event from the time of the *Exited* event. The Analysis Region data structure is extended to contain the following data element.

int nMinTime;

The second method for filtering false events is to define and detect a *Stop* state. Two constraints may be applied in order to define a stop state.

- maximum velocity: the maximum velocity, in inches per second, that an individual may not exceed to be deemed in a *Stop* state.

- minimum time: the minimum amount of time, in seconds, that the individual must maintain the maximum velocity constraint.

The Analysis Region data structure is extended to contain the following data
5 elements.

```
int      nMaximumStopVelocity;
int      nMinimumStopTime;
```

10 A second limitation of the reporting algorithm is the ability to manage the occurrence of multiple events occurring sequentially in time for the same region. This occurs when an individual is on the boundary of the Analysis Region and is moving in and out of the Analysis Region. In this instance, the report may contain multiple short events for the same region. For example, assume an individual entered the Analysis
15 Region at 10:10:05, departed the region at 10:10:55, entered the region at 10:10:57, and remained in the region until 10:12:05. A second example is described in the table below.

Region	Enter	Exit	Time In
Queue	10:10:05	10:10:08	3
Queue	10:10:11	10:10:14	3
Queue	10:10:16	10:10:25	9
Queue	10:10:27	10:10:33	6
Queue	10:10:38	10:10:45	7

20 While the individual maximum time in the zone is 9 seconds in the table above, it is readily apparent that the person was in the zone from 10:10:05 until 10:10:45, or 40 seconds.

Rather than reporting two or more distinct events, the system should merge the events into a single event. This can be done by searching the report for multiple events that occur in sequence for the same region. The Analysis Region data structure is extended to contain the following data element.

5

```
int          nMergeThreshold;
```

If the time between two sequential events for the same zone is less than the merge threshold, the two events should be merged into a single event.

10

By associating an activity with each Analysis Region, it becomes possible to identify types of behaviour. Typical types of behavior that may be of interest in a bank branch are: (1) customers performing self-service transactions, (2) customers performing transactions at staffed service points, and (3) customers leaving the bank without visiting a service point. Examples of classes of customer behavior in a retail store are: (1) a customer leaves the store without visiting a checkstand, (2) a customer shopping in a department or product category, (3) a customer waiting to checkout.

15

In order to detect types of behavior, activities are associated with each Analysis Region. In a bank branch, the activity associated with a queue is *the customer is waiting for service*. The activity associated with an ATM is *the execution of a self-service transaction*, while the activity associated with a Teller is *the execution of a staffed transaction*.

20

By analyzing the sequence and type of activities performed by the individual, it is possible to identify basic types of behaviors. The methodology used for analyzing and identifying types of behaviors or activities is that of the regular expression. The set of symbols, or the alphabet, may be created from the set of analysis regions or the set of activities. For example, one alphabet may consist of the set of regions and the

25

possible states, *Entered*, *Exited*, *Start*, *Stop*. The table below describes the alphabet for the bank branch previously described.

Region	State	Alphabet
Queue	<i>Entered</i>	A
Queue	<i>Exited</i>	B
Queue	<i>Start</i>	C
Queue	<i>Stop</i>	D
Teller	<i>Entered</i>	E
Teller	<i>Exited</i>	F
Teller	<i>Start</i>	G
Teller	<i>Stop</i>	H

- 5 The Track Report algorithm is updated to generate as output symbols from the defined alphabet. In order to identify a type of behavior, a regular expression is defined and the output is parsed to search for a match on a regular expression. For example, the regular expression that defines the behavior of waiting in a queue and being served at a teller is ABCD. This describes any path that enters and exits the queue and then enters and exits a teller location. A second example is the set of customers that wait in the queue and then visit two teller locations. This would be AB(CD)². By exploiting the minimum time constraint, it is possible to identify customer paths that experienced poor service. For example, if a queue wait time greater than 300 seconds is considered poor service, the minimum time constraint for the queue zone can be set to 300. The Track
- 10 Report algorithm only generates a Queue *Entered* and Queue *Exited* event if the person was in the region (Queue) for greater than 300 seconds. Now, the regular expression ABCD will only match paths of people that were in the queue greater than 300 seconds.
- 15

20 The alphabet for the regular expression parser can consist of symbols for every region of analysis in the floorplan, i. Teller 1, Teller 2, etc., or for classes of regions,

such as Tellers in general. This can be supported with the simple addition of a class descriptor to the region of analysis. Employees can be identified by defining areas that only employees may visit and then defining a grammar that describes employee activities. Similarly, an alphabet can be constructed from the set of behaviors that are associated with each region of analysis.

Similar to identifying types of behaviour, it is also possible to identify paths that may have been erroneously generated by the Single Tracking system by analyzing where the track originated, terminated, and where the track moved in the scene. For example, complete paths can be identified by creating a large region of analysis on the floorplan which encompasses all areas monitored by the camera with the exception of some border areas. In order to identify paths that may be incomplete due to errors in the Single Camera system, paths that originate inside this region are incomplete.

Three types of output may be produced by the Track Analysis system.

- A report of how where individuals went and spent time in the physical environment.
- A report of number of individuals to visit an area, as well as various statistics with regards to amount of time spent in the area.
- A file that consists of tracks sharing a common behavior.

An individual track report can be generated by outputting the results of track interpretation. For each track, an example report would consist of list of records containing

- Path ID,
- Region visited, and

- start time and end time for each region visited

An example report is shown below in a tabular structure that can be easily loaded into a relational database management system.

5

Path ID	Region	Start	End
1	Path	10:10:47	10:17:07
1	Queue 1	10:11:05	10:14:07
1	Teller 1	10:14:12	10:16:59
2	Path	10:10:52	10:16:57
2	Queue 1	10:11:13	10:12:00
2	Teller 7	10:12:02	10:16:40

By querying the individual track reports, it is possible to generate statistics with respect to each region of interest. The number of people to visit a region is calculated by counting the number of individual track reports that contain a record of a visit for the target region. The total number of people in a region at any moment in time can be calculated by counting the number of individual track reports where

10

start time < time of interest < end time.

The calculation for the average amount of time a person spends in a particular region is shown below.

15

$$\left(\sum_{i=0}^{i < \text{NumberOfTracks}} (\text{EndTime}_i - \text{StartTime}_i) \right) / \text{NumberOfTracks} .$$

The specification for the present invention provided above is intended to describe an implementation of the present invention in known and preferred embodiments, and is not intended as an exhaustive description of every possible way to

20

implement the invention. For example, the present invention may be used in a countless variety of situations where people, animals or objects are to be tracked and analyzed, and a variety of different methods may be used for analyze and utilizing the resulting data.

01
02
03
04
05
06
07
08
09
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214